

1. Reach-in Refrigerators & Freezers



Top mounted reach -In Refrigerators

Models	Description	Page
IRR-AGB23	1 Solid Door Refrigerator - 23 ft ³	20
IRR-AGB23_2	2 Solid Door Refrigerator - 23 ft ³	20
IRR-AGB49	2 Solid Door Refrigerator - 49 ft ³	20
IRR-AGB49_4	4 Solid Door Refrigerator - 49 ft ³	20
IRR-AGB23BT	1 Solid Door Freezer - 23 ft ³	20

IRR-AGB23BTR	1 Glass Door Freezer- 23 ft ³	20
IRR-AGB49BT	2 Solid Door Freezer- 49 ft ³	20
IRR-AGB23CR	1 Glass Door Refrigerator - 23 ft ³	20
IRR-AGB49CR	2 Glass Door Refrigerator - 49 ft ³	20
IRR-AGB901PDCR	2 Glass Door Refrigerator Pass Thru Extra Wide - 27,7 ft ³	22
IRR-AGB901PDC	2 Solid Door Refrigerator Pass Thru Extra Wide - 27,7 ft ³	22
IRR-AGB701PDCR	2 Glass Door Refrigerator Pass Thru - 19,7 ft ³	22
IRR-AGB701PDC	2 Solid Door Refrigerator Pass Thru - 19,7 ft ³	22
IRR-AGB1402PDCR	4 Glass Door Refrigerator Passthru - 43,7 ft ³	22
IRR-AGB1402PDC	4 Solid Door Refrigerator Pass Thru - 43,7 ft ³	22

Roll-In & Roll-thru

Models	Description	Page
IRR-AGB45RI	1 Section Roll-In Refrigerator With 66-1/4" Cart Capacity	21
IRR-AGB96RI	2 Section Roll-In Refrigerator With 66-1/4" Cart Capacity	21
IRR-AGB45RT	1 Section Roll-Thru Refrigerator With 66-1/4" Cart Capacity	21
IRR-AGB45RIBT	1 Section Roll-Thru Freezer With 66-1/4" Cart Capacity	21



Bottom mounted reach-In, Refrigerators & freezers

Models	Description	Page	Models	Description	Page
IRR-AN23	1 Solid Door Refrigerator - 23 ft ³	24	IRR-AN49MX	2 Solid Door Dual Refrigerator & Freezer - 49 ft ³	24
IRR-AN23_2	2 Solid Door Refrigerator - 23 ft ³	24	IRR-AN23CR	1 Glass Door Refrigerator - 23 ft ³	24
IRR-AN49	2 Solid Door Refrigerator - 49 ft ³	24	IRR-AN49CR	2 Glass Door Refrigerator 49 ft ³	24
IRR-AN49_4	4 Solid Door Refrigerator - 49 ft ³	24	IRR-AN67CR	3 Glass Door Refrigerator - 67 ft ³	24
IRR-AN67	3 Solid Door Refrigerator - 67 ft ³	24	IRR-AN23BTR	1 Glass Door Freezer - 23 ft ³	24
IRR-AN67_6	6 Solid Door Refrigerator - 67 ft ³	24	IRR-AN49BTR	2 Glass Door Freezer 49 ft ³	24
IRR-AN23BT	1 Solid Door Freezer - 23 ft ³	24			
IRR-AN49BT	2 Solid Door Freezer - 49 ft ³	24			
IRR-AN67BT	3 Solid Door Freezer - 67 ft ³	24			



Top mounted Slim Line reach-In, Refrigerators & freezers

Models	Description	Page	Models	Description	Page
IRR-AGN300CR	1 Glass Door Refrigerator	26	IRR-AGN602	2 Solid Door Refrigerator	26
IRR-AGN301	1 Solid Door Refrigerator	26	IRR-AGN603	3 Solid Door Refrigerator	26
IRR-AGN302	2 Solid Door Refrigerator	26	IRR-AGN604	4 Solid Door Refrigerator	26
IRR-AGN301BT	1 Solid Door Freezer	26	IRR-AGN602BT	2 Solid Door Freezer	26
IRR-AGN600CR	2 Glass Door Refrigerator	26	IRR-AGN602MX	2 Solid Door Dual Refrig. & Freezer	26



Specifications



Triple chamber snap in door gasket for easy cleaning



Reinforced shelves



Compact monoblock system [AGB models]



AGB23



AN23_2



AGB 1402 PDCR

Exterior

- AISI 304 stainless steel [AGN Series]
- AISI 430 stainless steel [AN and AGB Series]

Interior

- AISI 304 stainless steel [AGN Series]
- AISI 430 stainless steel [AN and AGB Series]
- Sealed interior floors and rounded cabinet corners
- Led lighting
- Internal drain plug for easy cleaning.

Shelving

- Three plastic coated wire shelves per door with stainless steel tray slides included.
- Tray slides are compatible with 18"x26" and 12"x20" sheet pans

Doors

- Polyurethane insulated doors,
- Self closing doors with stay open feature
- Stainless Steel heavy-duty hinges
- Triple chamber snap in door gaskets for easy removal and cleaning,
- Field reversible doors,
- Doors locks,
- Full-height door opening [22-7/8" x 58-5/8"].



Stainless steel interior and pre-installed tray-slides from the factory.



Expansion valve AGB models and AN model freezers



New Digital Controller EVCO



Universal Tray Slide [Standard]



AN67

Refrigeration

- Forced air refrigeration system, expansion valve
- Digital temperature controller with automatic defrost system
- Energy-saving non-electric condensate pan
- Evaporator coil coated with anticorrosion material 100% Polyester -100 °F ambient
- Electronic fans
- Hot gas defrost for low temp units



AGB45 RI

Roll-in & roll-thru

Exterior

- Insulated bottom 0,8" with 1 inch thick floor ramp included
- Built with removable panel for easy installation

Interior

- AISI 304 stainless steel
- Panel thickness 3-3/16"

Refrigeration

- Compact refrigeration system monoblock, INFRIBLOCK ®

Top mounted Reach-in Refrigerators & Freezers

AGB Series

Compact monoblock system



STANDARD

Expansion valve



IRR-AGB49CR

IRR-AGB23

Door lock

Compatible with 18" x 26" and 12" x 20" sheet pans

Full-height door opening
[22-7/8" x 58-5/8"]

RGB LED STANDARD
on-glass door



MOD.	Overall Dimensions			Doors	Shelves	(°F)	(ft³)	(HP)	115V (Amps)	[Lbs]	DOE
IRR-AGB23	27	31-1/4	84	1	3	33°F/38°F	23.0	1/4	3.8	380	Hydrocarbon R-290
IRR-AGB23_2	27	31-1/4	84	2	3	33°F/38°F	23.0	1/4	3.8	380	Hydrocarbon R-290
IRR-AGB49	54-1/2	31-1/4	84	2	6	33°F/38°F	49.0	1/3	4.0	700	Hydrocarbon R-290
IRR-AGB49_4	54-1/2	31-1/4	84	4	6	33°F/38°F	49.0	1/3	4.0	700	Hydrocarbon R-290
IRR-AGB23BT	27	31-1/4	84	1	3	-5°F/0°F	23.0	3/4	7.2	375	Hydrocarbon R-290
IRR-AGB49BT	54-1/2	31-1/4	84	2	6	-5°F/0°F	49.0	1 -1/4	10.5	620	Hydrocarbon R-290
IRR-AGB23CR	27	31-1/4	84	1	4	33°F/38°F	23.0	1/3	5.0	380	Hydrocarbon R-290
IRR-AGB49CR	54-1/2	31-1/4	84	2	8	33°F/38°F	49.0	1/3	5.2	620	Hydrocarbon R-290
IRR-AGB23BTCR	27	31-1/4	84	1	4	-5°F/0°F	23.0	1/3	7.79	455	Hydrocarbon R-290

STANDARD FEATURES

ELECTRICAL	Cord and NEMA 5-15P plug, electrical connection is 115V / 1ph / 60Hz Expansion valve (all) and hot gas defrost system (BT)		Cord and NEMA 5-15P plug, (AGB 23BT)
DOE DOORS	BT Models: Heated door frame to avoid accumulation of ice		Door built-in Thermopane double glass (CR models)
AMBIENT	Temp 100°F		
OPTIONS Section 10 (Accessories & parts)	Stainless Steel wire shelves Stainless Steel tray divider		Additional slide kits Set of 6" legs, height adjustable from 5" to 8"