9. Dry aging





Dry aging meat cabinet

Models IMD-AGB701MDA IMD-AGB701MDAB IMD-AGB701MDAB IMD-AGB1402MDAB IMD-VC1400MDA IMD-VC1400MDAB IMD-AGB2010MDAB IMD-AC140MDAB IMD-AC280MDAB

徽

Description Dry aging meat cabinet- 1 glass door Dry aging meat cabinet- 2 glass door Dry aging meat cabinet- 1 glass door Dry aging meat cabinet- 2 glass door 3/4 Vision counter case VC series Dry aging meat cabinet AGB Series Dry aging meat cabinet AGB Series

92

92



AGING MEAT

9 DRY

87

Our highly efficient controllers allow the atmosphere to be maintained at a specific and stable temperature and humidity for the correct maturation of the meat.

Proper airflow, the careful arrangement of pieces with adequate spacing, and precise control of water evaporation from within the muscles are essential to the process. This results in the loss of about one-fifth of the volume while intensifying the flavors

The ideal environment is 37.5°F with a humidity between 50-60% and the pieces must remain for at least 28 days, although each type of meat is different .















Boy

37.5° 60°

ли (U) | ∨ |∧лих| ♀ | ветс)

Door Open

80



str Infrico





The maturation process occurs in a controlled environment, where the meat is exposed to carefully regulated conditions of temperature, humidity, and air quality.

With our maturation process, meat achieves unbeatable tenderness, flavor, and juiciness. This time-honored technique has been modernized by Infrico, allowing our customers to age their meat to perfection and showcase these little gems that are sure to impress their guests.

Dry aging meat cabinets

IMD-AGB1402MDA



AGBSeries

NEW PRODUCT

					ŀ	J		Ĵţ	(Amps)	\langle	
	MOD.	Overall Dimensions		Doors	(°F)	[ft ³]	[HP]	115V	[Lbs]	DOE	
NEW	IRR-AGB701MDA	27	31-3/8	83-1/2	1	32°F/61°F	19,7	1/3	7,20	370	Hydrocarbon R-290
NEW	IRR-AGB701MDAB	27	31-3/8	83-1/2	1	32°F/61°F	19,7	1/3	7,20	370	Hydrocarbon R-290
NEW	IRR-AGB1402MDA	54-3/8	31-3/8	83-1/2	2	32°F/61°F	27,7	3/4	12,54	458	Hydrocarbon R-290
NEW	IRR-AGB1402MDAB	54-3/8	31-3/8	83-1/2	2	32°F/61°F	27,7	3/4	12,54	458	Hydrocarbon R-290
NEW	IMD-VC1400MDA	54-1/2	29-3/8	41-5/8	2	32°F/61°F	16,6	1/3	9,61	343	Hydrocarbon R-290
NEW	IMD-VC1400MDAB	54-1/2	29-3/8	41-5/8	2	32°F/61°F	16,6	1/3	9,61	343	Hydrocarbon R-290
NEW	IMD-VC2010MDA	79-1/8	29-3/8	41-5/8	3	32°F/61°F	25,07	1/3	9,66	467	Hydrocarbon R-290
NEW	IMD-VC2010MDAB	79-1/8	29-3/8	41-5/8	3	32°F/61°F	25,07	1/3	9,66	467	Hydrocarbon R-290